


Features & Description

- Easy to terminate, compact jack
- Work in standard keystone opening
- Beryllium copper contact for superior connectivity
- IDC contact design eliminates need to strip individual conductors
- Insulations displacement contacts (IDC) ensure highest quality, highest reliability
- termination available
- Can be re-terminated a in number of 250 times

Physical Specifications

- Apply UL-94V high-impact, fire retardant ABS Material
- Beryllium copper contact:50-μ" gold- plated pins over 100-μ" nickel layer
- Insertions life cycle :1,000 cycles (min.)/I.D.C. 250 cycles (min)
- Plug & jack contact force:100g
- IDE:22-26 AWG wires
- Plug retention force: 30 lb (min.)
- Feature staggered plug contacts
- Include dust cover for dust and dampness protections
- FCC Part 68 UL Certified
- Operating temperature:-40°C to +68°C



Electrical Characteristics

- Insulation Resistance : 500M.
- Contact Resistance : 20M.
- Current rating : 1.5 Amps
- DC Resistance : Max. 0.1
- Dielectric withstand V: 1,000 VAC RMS @ 60 Hz/1 min.

Standards

- EIA/TIA568.B2
- ISO 11801 2nd. Version
- EN 50173-1

Applications

- 10 BaseT, 100BaseTX, 1000BaseT
- 4-16Mbit Token Ring
- 622-155Mbit ATM
- ISDN
- Analog Voice

Ordering Information:

Part No:
KJ-C5E-U
KJ-C5E-UT
KJ-C5E-F

Description:

XPcable Cat5e UTP Keystone Jack
XPcable Cat5e UTP Keystone Jack Toolless
XPcable Cat5e FTP Keystone Jack



ELECTRONICS CO., LTD.

RM A206, 11FL., No. 51 Hengyang Road, Taipei 100, Taiwan, R.O.C.

www.xpcable.com